

"Enhancing Product Quality & Profits"

"Stainless Programmable Short Cycle"

FREEZE DRYER





PRICED AT \$569,900

(550 POUNDS/16-24 HOURS)

The FC-R Range of short cycle freeze dryers use radiant heat energy, and a rapid load/unload trolley and cassette system.

Simply pre-freeze your product in a walk-in freezer, roll the trolleys to the freeze dryer, and slide the cassettes into the product chamber. Loading and unloading takes just minutes.

Some of the key features of this unit are:

- Fast drying of 550 pounds of product in 16-24 hours
- o Fully programmable cycle with a 19 inch touch screen HMI

- Tray area of 264 square feet
 Shelf spacing of 3.15 inches
 Supplied with 2 trolleys, 2 cassettes, and 2 sets of trays (88 x
- This freeze dryer is supplied with a 60 KW Chiller

Built to exacting specifications at our ISO:9001 Factory.

CE Certified

Onsite commissioning will be completed by a NutriFREEZE team member.

TECHNICAL DATA FC-R 250

| CONTROL SYSTEM: | Fully Programmable |
|----------------------------|------------------------------------|
| ICE CONDENSER CAPACITY: | Continuous Defrost |
| ICE CONDENSER | -67°F/-55°C |
| TEMPERATURE: | |
| DEFROSTING: | Continuous Cold Stream |
| NUMBER OF SHELVES: | 22 Shelves (88 Trays) |
| LOADING SYSTEM: | Cassette/Trolley |
| TOTAL SHELF AREA: | 264 Square Feet |
| SHELF TEMPERATURE: | Up to +266°F/+130°C |
| REFRIGERATION: | Two Stage Compressor |
| REFRIGERANT: | R-404A |
| COOLING SYSTEMS: | 60 KW Chiller-Water/Glycol |
| VACUUM SYSTEM: | Pfeiffer Duo 125 |
| ELECTRICAL SPECIFICATIONS: | 460/480 Volt, 60 Cycle, 3 Phase |
| AMPERAGE: | 160 Amp Dedicated Line |
| UNIT DIMENSIONS: | 217 x 87 x 87 inches L x W x H |
| WEIGHT: | 12,125 Lbs |
| | |





NutriFREEZE

"Enhancing Product Quality & Profits"

"Stainless Programmable Short Cycle" FREEZE DRYER





GENERAL DATA

| 60 KW CHILLER | |
|---------------------------|------------|
| COOLING CIRCUITS | 1 |
| COMPRESSORS | 2 – Scroll |
| CAPACITY CONTROL | 0-50-100% |
| POWER | 460/3/60 |
| FANS | 1 – Axial |
| CONDENSER AIR FLOW | 11,413 cfm |
| POWER (EACH) | 1.03 kW |
| AVAILABLE STATIC PRESSURE | 0 "wc |
| TANK VOLUME | 92.5 gal |
| LENGTH | 89 in |
| WIDTH | 34 in |
| HEIGHT | 82 in |
| WEIGHT | 2202 lbs |
| AMPERAGE | 47 A |

PERFORMANCE

| 60 KW CHILLER | |
|---------------------------------|-----------------------------|
| REFRIGERANT | R410A |
| HYDRAULIC KIT | P3 |
| INLET WATER TEMPERATURE | 90°F |
| OUTLET WATER TEMPERATURE | 59°F |
| GLYCOL TYPE | 25% Propylene Glycol |
| AMBIENT TEMPERATURE | 95°F |
| COOLING CAPACITY | 18.3 Tons 219,600 Btu/Hr |
| TOTAL ABSORBED POWER | 24.8 kW |
| EVAPORATOR WATER FLOW RATE | 45.6 gpm |
| AVAILABLE HEAD PRESSURE | 39 psi |
| MAX AMBIENT TEMPERATURE | 110°F |



