



NutriFREEZE

"Enhancing Product Quality & Profits"

"Stainless Programmable Short Cycle"

FREEZE DRYER

**2025
STANDARD**



**MODEL
FC-R 50 +
15 KW CHILLER**

PRICED AT \$189,900
(110 POUNDS/16-24 HOURS)

The FC-R Range of short cycle freeze dryers use radiant heat energy, and a rapid load/unload trolley and cassette system.

Simply pre-freeze your product in a walk-in freezer, roll the trolley to the freeze dryer, and slide the cassette into the product chamber. Loading and unloading takes just minutes.

Some of the key features of this unit are:

- Fast drying of 110 pounds of product in 16-24 hours
- Fully programmable cycle with a 19 inch touch screen HMI
- Tray area of 52 square feet
- Shelf spacing of 3.15 inches
- Supplied with 1 trolley, 1 cassette, and 1 set of trays (16)
- This freeze dryer is supplied with a 15 KW Chiller

Built to exacting specifications at our ISO:9001 Factory.

CE Certified

Onsite commissioning will be completed by a NutriFREEZE team member.

TECHNICAL DATA

FC-R 50

CONTROL SYSTEM:	Fully Programmable
ICE CONDENSER CAPACITY:	165 Pounds
ICE CONDENSER PERFORMANCE:	132 Lbs/24 Hrs
ICE CONDENSER TEMPERATURE:	-67°F/-55°C
DEFROSTING-END OF LOAD:	Hot Gas
NUMBER OF SHELVES:	8 Shelves (16 Trays)
LOADING SYSTEM:	Cassette/Trolley
TOTAL SHELF AREA:	52 Square Feet
SHELF TEMPERATURE:	Up to +266°F/+130°C
REFRIGERATION:	Two Stage Compressor
REFRIGERANT:	R-404A
COOLING SYSTEMS:	15 KW Chiller-Water/Glycol
VACUUM SYSTEM:	Pfeiffer Duo 35
ELECTRICAL SPECIFICATIONS:	460/480 Volt, 60 Cycle, 3 Phase, Other Voltages Available
AMPERAGE:	40 Amp Dedicated Line
UNIT DIMENSIONS:	115 x 67 x 83 Inches L x W x H
WEIGHT:	4,409 Lbs



BOTANIQUE PRESERVATION EQUIPMENT, INC.
Phoenix, Arizona USA 85050



PHONE: 623-977-8900
WEBSITE: www.nutrifreeze.net
EMAIL: rldelong@nutrifreeze.net

(1/1/25)

NutriFREEZE

"Enhancing Product Quality & Profits"

"Stainless Programmable Short Cycle"
FREEZE DRYER

2025
STANDARD

MODEL FC-R 50 - 15 KW CHILLER



GENERAL DATA

15 KW CHILLER	
COOLING CIRCUITS	1
COMPRESSORS	1 – Scroll
CAPACITY CONTROL	0-100%
POWER	460/3/60
FANS	1 – Axial
CONDENSER AIR FLOW	3,590 cfm
POWER (EACH)	0.76 kW
AVAILABLE STATIC PRESSURE	0 "wc
TANK VOLUME	30.4 gal
LENGTH	52 in
WIDTH	26 in
HEIGHT	55 in
WEIGHT	765 lbs
AMPERAGE	13 A

PERFORMANCE

15 KW CHILLER	
REFRIGERANT	R410A
HYDRAULIC KIT	P3
INLET WATER TEMPERATURE	90°F
OUTLET WATER TEMPERATURE	59°F
GLYCOL TYPE	25% Propylene Glycol
AMBIENT TEMPERATURE	95°F
COOLING CAPACITY	5.12 Tons 61,440 Btu/Hr
TOTAL ABSORBED POWER	6.33 kW
EVAPORATOR WATER FLOW RATE	12.8 gpm
AVAILABLE HEAD PRESSURE	39 psi
MAX AMBIENT TEMPERATURE	110°F



BOTANIQUE PRESERVATION EQUIPMENT, INC.
Phoenix, Arizona USA 85050



PHONE: 623-977-8900
WEBSITE: www.nutrifreeze.net
EMAIL: rldelong@nutrifreeze.net

(1/1/25)